

# Titan™ Dual and Single Coffee Brewers

High-volume brewing solution featuring simple operation, precise extraction control and portable servers



**Titan Dual Brewer**  
(server sold separately)



**Titan Single Brewer**  
(server sold separately)



**Titan TF Server**

## PRODUCT FEATURES

- Dual brews 34.3 gallons (129.8 litres) of perfect coffee per hour.
- Single brews 22.5 gallons (85.2 litres) of perfect coffee per hour.
- Coffee extraction controlled with pre-infusion and pulse brew, digital temperature control, and large sprayhead; variable by-pass controls coffee strength.
- BrewMETER® allows automatic programming of pulse routine.
- SplashGard® funnel and funnel locks help improve safety.
- Funnel has 28 ounce (.8 litre) capacity and paper filter retainers to eliminate fold-over.
- ThermoFresh® servers are insulated to keep coffee hot for hours.
- Left or right faucet for hot water.
- Energy saver mode reduces tank temperature during idle periods.
- Use BUNN paper filter – Product No. 20111.0000.

## TITAN TF SERVER

- Insulated server keeps coffee hot for hours.
- Contemporary styling and wrap program for maximum merchandising.
- Large cup clearance allows for dispensing into cups, decanters and thermal carafes.
- Brew-through lid.
- Integrated sight gauge assembly allows for easy cleaning.
- Designed for use with Titan brewers.

## Titan 3 Gallon Coffee Brewers

Model	Product #	Size		Electrical			Brewing Capacity	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts			
Titan Dual	39200.0000	40"H x 35.6"W x 21.7"D (101.7cm H x 90.5cm W x 55.2cm D)	148 lbs. (67.1 kg)	120/208 (3 phase)	33.4	12000	34.3 gal./hr. 129.8 L/hr.	No	 
				120/208 (1 phase)	40.1	8200	22.9 gal./hr. 86.7 L/hr.		
Titan Single	39300.0000	40.02" H x 21.3" W x 21.74" D (101.7cm H x 54.1cm W x 55.2cm D)	107 lbs. (48.5 kg)	120/208 (3 phase)	33.4	12000	22.5 gal./hr. 85.2 L/hr.		
				120/208 (1 phase)	40.1	8200	17 gal./hr. 64.4 L/hr.		
Titan TF Server	39400.0001	23.7"H x 13.7"W x 17.1"D (60.2cm H x 34.8cm W x 43.4cm D)	17.5 lbs. (7.9 kg)	n/a	n/a	n/a			

# BrewWISE® ThermoFresh® Brewers



**BrewWISE Dual TF**  
(server sold separately)



**BrewWISE Single TF**  
(server sold separately)



**BrewWISE Recipe Writer**  
(requires recipe cards - sold separately)

The Single and Dual TF brewers use vacuum-insulated ThermoFresh servers.





## PRODUCT FEATURES

- Brews ½, 1, or 1½ gallon (1.9, 3.8 or 5.7 litre) batches.
- Stores individual coffee recipes.
- Large sprayhead and BrewWISE intelligence with pre-infusion and pulse brew for maximum flavor extraction.
- Variable by-pass controls coffee strength.
- Wireless brewer-grinder interface via Smart Funnel® with SplashGard®.
- Simplify installation and calibration by creating coffee recipe cards and dedicated funnels with the Recipe Writer using your PC (U.S. and English MS Windows® compatible).
- Equipped with tank drain.
- Use BUNN paper filter – Product No. 20138.0000.
- Compatible with BUNNlink®.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

 International electrical configurations

## BrewWISE Single and Dual ThermoFresh DBC Brewers

Model	Product #	Size		Finish	Electrical			Brewing Capacity	Funnel Locks	Cord Attached	Agencies			
		Dimension	Weight		Volts	Amps	Watts							
Single TF DBC	34800.0000	35.7" H x 12.1" W x 19.2" D (90.7cm H x 30.7cm W x 48.8cm D)	59 lbs. (26.8 kg)	Stainless	120/240	16.6	4000	11.4 gal./hr. 43.2 L/hr.	Yes	No	 			
	34800.0002				120/208	19.2			No					
	34800.0003				120/208	19.2			Yes					
	34800.0004			35.7" H x 12.1" W x 19.2" D (90.7cm H x 30.7cm W x 48.8cm D)	59 lbs. (26.8 kg)	Black	120/240	16.6	4000			11.4 gal./hr. 43.2 L/hr.	No	
	34800.0001						120	18.1					2200	6.5 gal./hr. 24.6 L/hr.
	34800.0008					Stainless	120	18.1	2200			6.5 gal./hr. 24.6 L/hr.	Yes	No
	34800.0017													
Dual TF DBC	34600.0000	35.7" H x 21.8" W x 20.2" D (91.7cm H x 55.4cm W x 51.3cm D)	92.5 lbs. (42 kg)	Stainless	120/240	27.5	6600	18.9 gal/hr 71.5 L/hr.	No	No	 			
	34600.0001			Black										
	34600.0002			Stainless										
	34600.0003			Black	120/208	27.4	5700	16.3 gal/hr 61.7 L/hr.	Yes					
	34600.0004			Stainless										
	34600.0005			Black										
	34600.0006			Stainless	27.4	5700	16.3 gal/hr 61.7 L/hr.	Yes						
	34600.0007			Black	27.4									
Recipe Writer	34444.0000	2.2" H x 6.4" W x 9.5" D (5.6cm H x 16.2cm W x 21.4cm D)	6.1 lbs. (2.8 kg)	Black	120	1	n/a	n/a	n/a	n/a				
Recipe Card	34447.0000	n/a	1.2 lbs.	n/a										
Ad Card	34448.0000	n/a	1.2 lbs.	n/a										

# Digital ThermoFresh® Servers and Stand



## COMMON FEATURES

- Vacuum insulated.
- Digital sight gauge creates more room for merchandising wrap.
- Four-hour digital indicator display in 15-minute segments.
- Volume indicator display.
- Digital sight gauge operates on four AAA batteries with an average 1-year lifespan. Display shows low battery symbol.
- Fast flow faucet.
- Brew-through lid.

## TF SERVER WITH BASE

- Built-in drip tray easily removed for cleaning.
- 7.7" (19.6 cm) cup clearance.
- Stackable design for dry storage.

## DIGITAL TF SERVER WITH COUNTDOWN TIMER

- Four-hour digital indicator displays in 1-minute increments.

## TF BASELESS SERVER

- 7.05" (17.9 cm) cup clearance.
- Use with the TF Server Stand for easy dispensing. Product No. 39795.0000

1 Gal TF Server

Digital ThermoFresh Servers										
Model	Product #	Size		Electrical			Finish	Holding Capacity	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts				
TF Server	39500.0050	21.1" H x 9.3" W x 13.1" D (53.6cm H x 23.6cm W x 33.3cm D)	13 lbs (5.9 kg)	n/a	n/a	n/a	SST	1 gal (3.8 litre)	No	NSF
	Black									
	39550.0050	23.1" H x 9.3" W x 13.1" D (58.7cm H x 23.6cm W x 33.3cm D)	14 lbs. (6.4 kg)				SST	1.5 gal (5.7 litre)		
	Black									
DSG TF Server (countdown timer)	39500.0100	21.1" H x 9.3" W x 13.1" D (53.6cm H x 23.6cm W x 33.3cm D)	13 lbs (5.9 kg)	n/a	n/a	n/a	SST	1 gal (3.8 litre)	No	NSF
	39550.0100	23.1" H x 9.3" W x 13.1" D (58.7cm H x 23.6cm W x 33.3cm D)	14 lbs. (6.4 kg)				SST	1.5 gal (5.7 litre)		
Digital ThermoFresh Servers (baseless) and Stand										
TF Server	39500.0054	13.1" H x 9.1" W x 13.1" D (33.3cm H x 23.11cm W x 33.3cm D)	13 lbs (5.9 kg)	n/a	n/a	n/a	SST	1 gal (3.8 litre)	No	NSF
	Black									
	39550.0054	15.1" H x 9.1" W x 13.1" D (38.35cm H x 23.11cm W x 33.3cm D)	14 lbs (6.4 kg)				SST	1.5 gal (5.7 litre)		
	Black									
TF Server Stand	39795.0000	8.7" H x 9.4" W x 12.9" D (22.1cm H x 23.9cm W x 32.8cm D)	4.2 lbs (1.9 kg)				Black	n/a		n/a

# ThermoFresh® Servers and Stand



Baseless 1 Gal TF Server



TF Server Stand



1.5 Gal TF Server

## COMMON FEATURES

- Vacuum insulated.
- Easily transport coffee to remote locations.
- Fast flow faucet.
- Brew-through lid.

## TF SERVER WITH BASE

- Built-in drip tray attached to the server for transportation – easily removed for cleaning.
- 7.7" (19.6 cm) cup clearance.

## TF BASELESS SERVER

- 7.05" (17.9 cm) cup clearance.
- Use with the TF Server Stand for easy dispensing. Product No. 39795.0000

TF Servers	For Use With	Page #
with base - digital or mechanical gauge	Single TF DBC	4
	Dual TF DBC	
	ICB Tall	14
	ICB Twin Tall	
baseless - digital or mechanical gauge with adapter ring, sold separately	Single SH DBC	9
	Dual SH DBC	
	Single SH	8
	Dual SH	
baseless - digital or mechanical gauge	ICB	13
	ICB-Twin	

## ThermoFresh Servers

Model	Product #	Size		Electrical			Finish	Holding Capacity	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts				
TF Server	39500.0000	20.8" H x 9.3" W x 13.2" (52.8cm H x 23.6cm W x 33.5cm D)	13 lbs. (5.9 kg)	n/a	n/a	n/a	SST	1 Gallon (3.8 L)	No	NSF
	39500.0001						Black			
	39550.0000	22.9" H x 9.3" W x 13.2" D (58.2cm H x 23.6cm W x 33.5cm D)	14 lbs. (6.4 kg)				SST	1.5 Gallon (5.7 L)		
	39550.0001						Black			

## ThermoFresh Servers (baseless) and Stand

Model	Product #	Size		Electrical			Finish	Holding Capacity	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts				
TF Server	39500.0004	12.8" H x 9.1" W x 13.1" D (32.5cm H x 23.1cm W x 33.3cm D)	10 lbs. (4.5 kg)	n/a	n/a	n/a	SST	1 Gallon (3.8 L)	No	NSF
	39500.0005						Black			
	39550.0004	14.9" H x 9.1" W x 13.2" D (37.8cm H x 23.1cm W x 35.1cm D)	11 lbs. (5.0 kg)				SST	1.5 Gallon (5.7 L)		
	39550.0005						Black			
TF Server Stand	39795.0000	8.7" H x 9.4" W x 12.9" D (22.1cm H x 23.9cm W x 32.8cm D)	4.2 lbs (1.9 kg)				Black	n/a		n/a

# BrewWISE® Soft Heat® DBC® Brewers



**BrewWISE Dual SH DBC**  
(server sold separately)







**BrewWISE Single SH DBC**  
(server sold separately)

## PRODUCT FEATURES

- Brews ½, 1, or 1 ½ (1.9, 3.8 or 5.7 litre) gallon batches.
- Stores individual coffee recipes.
- Large sprayhead and BrewWISE intelligence with pre-infusion and pulse brew for maximum flavor extraction.
- Variable by-pass controls coffee strength.
- Dual holds two 1½ gallon (5.7 litre) SH servers. Single holds one server.
- Wireless brewer-grinder interface via Smart Funnel® with SplashGuard®.
- Simplify installation and calibration by creating coffee recipe cards and dedicated funnels with the Recipe Writer using your PC (U.S. and English MS Windows® compatible).
- Equipped with tank drain.
- Use BUNN paper filter – Product No. 20138.0000.
- Compatible with BUNNlink®.

*Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.*

 International electrical configurations

BrewWISE Single and Dual Soft Heat DBC Brewers											
Model	Product #	Size		Finish	Electrical			Faucet Location	Brewing Capacity	Cord Attached	Agencies
		Dimension	Weight		Volts	Amps	Watts				
Single SH DBC	33600.0000	35.8"H x 9.3"W x 23.1"D (90.9cm H x 23.6cm W x 58.7cm D)	59 lbs. (26.8 kg)	Stainless	120/240	17.5	4100	Upper	11.4 gal/hr 43.2 L/hr.	No	 
	Black										
	33600.0013										
Dual SH DBC	33500.0000	35.8"H x 18"W x 21.2"D (90.9cm H x 45.7cm W x 53.8cm D)	90 lbs. (40.8 kg)	Stainless	120/240	29.1	6800	Upper	18.9 gal/hr 71.5 L/hr.	No	 
	89 lbs. (40.4 kg)		Black								
	33500.0004										
	33500.0006		90 lbs. (40.8 kg)	Stainless				Lower			

# Soft Heat® Brewers



**Dual SH**  
(server sold separately)




**Single SH**  
(server sold separately)



## PRODUCT FEATURES

- Variable batch selector knob allows ½, 1 or 1½ gallon (1.9, 3.8 or 5.7 litre) batches.
- Electronic grinder interface instructs grinder on exact amount of coffee for selected brew batch size.
- Dual holds two 1½ gallon (5.7 litre) SH servers. Single holds one server.
- Patented Soft Heat® server heat control automatically shuts off once target temperature is reached. Can be set to 175°-190°F (79.4° - 87.8°C).
- Remote 1 or 2 server docking stations (sold separately).
- Equipped with tank drain.
- Use BUNN paper filter – Product No. 20138.0000.

*Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.*

 International electrical configurations

## Single and Dual Soft Heat Brewers

Model	Product #	Size		Finish	Electrical			Capacity	Cord Attached	Agencies
		Dimension	Weight		Volts	Amps	Watts			
Single SH	27800.0001	35.8"H x 9.3"W x 20.2"D (90.9cm H x 23.6cm W x 50.8cm D)	61 lbs. (27.7 kg)	Stainless	120/208	18.3	3800	10.6 gal/hr 40.1 L/hr.	No	
	27800.0002		59 lbs. (26.8 kg)		120/240	17.9	4300	11.4 gal/hr 43.2 L/hr.		
	27800.0009		57 lbs. (25.9 kg)		120	17.5	2100	5.1 gal/hr 19.3 L/hr.		
Dual SH	27900.0001	35.8"H x 18"W x 20.5"D (91cm H x 45.7cm W x 52.1cm D)	90 lbs. (40.9 kg)	Black	120/208	28.3	5900	16.3 gal/hr 61.7 L/hr.	No	
	27900.0002		89 lbs. (40.4 kg)		120/240		6800	18.9 gal/hr 71.5 L/hr.		
	27900.0020		90 lbs. (40.9 kg)		120/208		5900			

# Soft Heat® Servers and Stands




**1 SH Server and Docking Station**



**2SH Docking Station**

## SOFT HEAT® SERVER FEATURES

- Soft Heat® servers supply controlled heat to coffee.
- LED power indicator.
- Safety-Fresh® patented brew-through lid with vapor seal and spill prevention.







 International electrical configurations

## SOFT HEAT DOCKING STATION FEATURES

- Remote one and two server docking stations.
- Instant power contact with servers.

 International electrical configurations

	For Use With	Page #
Soft Heat Server	Single SH DBC	7
	Dual SH DBC	
	Single SH	8
	Dual SH	

Soft Heat Servers and Docking Stations												
Model	Product #	Size		Finish	Electrical			Capacity	Setting	Legs	Cord Attached	Agencies
		Dimension	Weight		Volts	Amps	Watts					
1SH Stand	27825.0000	28.2"H x 10"W x 14"D (71.6cm H x 25.4cm W x 35.6cm D)	13 lbs. (5.9 kg)	Stainless	120	0.75	90	1 SH Server	N/A	4"	Yes	 
	27825.0004		Black	6"								
	27825.0003		Black	6"								
2SH Stand	27875.0000	11.6"H x 18.7"W x 13.2"D (29.5cm H x 47.5cm W x 33.5cm D)	22 lbs. (10 kg)	Stainless	1.5	180	2 SH Servers	N/A	4"	Yes	 	
	27875.0003		Black	4"								
SH Server	27850.0001	16.6"H x 8.5"W x 14" D (42.2cm H x 21.6cm W x 35.6cm D)	17 lbs. (7.8 kg)	Stainless	n/a	n/a	n/a	1 1/2 Gal	n/a	n/a	Yes	 
	27850.0004		18 lbs. (8.2 kg)	Black				30 Min.				
	27850.0006		17 lbs. (7.8 kg)	Stainless				45 Min.				
	27850.0008			Black				60 Min.				
	27850.0016			Stainless				240 Min.				
	27850.0022			Black				120 Min.				

# Single® and Dual® Brewers



Dual



Single





## PRODUCT FEATURES

- Brews ½, 1 or 1½ gallon (1.9, 3.8 and 5.7 litre) batches.
- Adjustable bypass ensures perfect coffee regardless of batch size.
- Electronic timer ensures fast set up and accurate brew levels.
- Electronic grinder interface instructs G9T HD grinder on exact amount of coffee for selected brew batch size.
- 1.5 GPR portable server (included) has a patented Safety-Fresh® brew-through lid with vapor seal and spill protection.
- SplashGard® funnel deflects hot liquids away from the hand.
- Equipped with tank drain.
- Use BUNN paper filter – Product No. 20138.0000.

*Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.*

 International electrical configurations

## Single and Dual Brewers with Portable Servers

Model	Product #	Size		Finish	Electrical			Brewing Capacity	Batch Settings	Funnel Type	Cord Attached	Agencies
		Dimension	Weight		Volts	Amps	Watts					
Single	23050.0006	29.3"H x 9.25"W x 19"D (74.4cm H x 54.9cm W x 48.3cm D)	57 lbs. (25.9 kg)	Stainless	120	17.5	2100	5.1 gal/hr 19.3 L/hr.	One	Plastic	No	 
	23050.0007		58 lbs. (26.3 kg)				2100					
	23050.0010		59 lbs. (26.8 kg)		120/208	18.3	3800	10.6 gal/hr 40.1 L/hr.	Three	Stainless		
	23050.0011				120/240	17.9	4300	11.4 gal/hr 43.2 L/hr.				
Dual	20900.0008	29.3"H x 18"W x 19.3"D (74.4cm H x 45.7cm W x 49cm D)	92 lbs. (41.8 kg)	Stainless	120/208	28.8	5990	16.3 gal/hr 67.7 L/hr.	One	Plastic	No	 
	20900.0010		94 lbs. (42.7 kg)									
	20900.0011		95 lbs. (43.1 kg)		120/240	28.7	6890	18.9 gal/hr 71.5 L/hr.	Three	Stainless		

# 1 Gallon Automatic Brewer



Single CWTF

## SINGLE CWTF FEATURES

- Brew half gallon and 1 gallon (1.9 and 3.8 litre) batches into included 1.5 GPR portable server.
- Gourmet funnel models allows use of heavier throw weights of coffee.
- 1.5 GPR portable server (included) has a patented Safety-Fresh® brew-through lid with vapor seal and spill protection.
- SplashGard® funnel deflects hot liquids away from the hand.
- All stainless steel construction.
- Half gallon (1.9 litre) pourover backup.
- Gourmet funnel requires BUNN paper filter 20100.0000.

*Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.*

1 Gallon Automatic Coffee Brewer											
Model	Product #	Size		Finish	Electrical			Funnel Type	Brewing Capacity	Cord Attached	Agencies
		Dimension	Weight		Volts	Amps	Watts				
Single CWTF15	35000.0004	26.1"H x 8.5"W x 18.9"D (66.3cm H x 21.6cm W x 48cm D)	46.5 lbs. (21 kg)	Stainless	120	13.8	1650	Gourmet Stainless	3.8 gal/hr 14.4 L/hr.	Yes	UL LISTED
Single CWTF35	35000.0006				120/208-240	15.8	3650		7.5/9.0 gal/hr 28.4/34.1 L/hr.	No	NSF

# Portable Servers and Warmers



**1.5 GPR**  
Portable Server



**RWS1**  
Warmer

## PORTABLE SERVER FEATURES

- 1 or 1½ gallon (3.8, 5.7 litre) capacities.
- Easily transport portable servers for remote service.
- Patented Safety-Fresh® brew-through lid with vapor seal and spill protection GPR servers.

## WARMER FEATURES

- Accepts 1 or 1½ gallon (3.8, 5.7 litre) servers.
- Available with plastic, satin nickel or stainless steel legs.
- Legs are adjustable on RWS1



International electrical configurations

GPR Server	For Use With	Page #
	Single	10
	Dual	
	Single CWTF	11
Single CDF		

## Portable Servers and Warmers

Model	Product #	Size		Finishes	Electrical			Capacity	Cord Attached	Agencies	
		Dimension	Weight		Volts	Amps	Watts				
<b>1GPR</b> (bail handle)	12487.0001	14"H x 8.5"W x 12.7"D (35.6cm H x 21.6cm W x 32.2cm D)	8.5 lbs. (3.9 kg)	Stainless	n/a	n/a	n/a	1 gal 3.8 L	n/a		
<b>1GPR</b> (side handle)	12487.0003		9 lbs. (4.1 kg)								
<b>1GPR-FF</b> (bail handle, fast flow faucet)	12487.0005		10 lbs. (4.5 kg)								
<b>1.5GPR-FF</b> (top handle, fast flow faucet)	20950.0004	18.1"H x 8.5"W x 12.7"D (46cm H x 21.6cm W x 32.2cm D)	10 lbs. (4.5 kg)		120	0.8	100	1 1/2 gal 5.7 L	Yes		 
<b>RWS1</b> (plastic legs)	12203.0010	7.5" H x 8.25" W x 9.3" D (19.1cm H x 21cm W x 23.6cm D)	7 lbs. (3.2 kg)								
<b>RWS1</b> (satin nickel legs)	12203.0014	9 lbs. (4.1kg)									