

Infusion Coffee Brewers



ICB-DV
(Airpot sold separately)



ICB-Twin
(TF Server sold separately)

COMMON FEATURES

- Three brew buttons allow for 3 separate brewing profiles. Two programmable batch switches for full and half batches.
- Brews into 2.5 to 3.8 litre airpots and 1 and 1.5 gallon (3.8 and 5.7 L) baseless ThermoFresh® servers.
- Large sprayhead and BrewWISE® intelligence with pre-infusion and pulse brew for maximum flavor extraction. DBC grinder communicates with brewer through Smart Funnel®.
- Energy-saver mode reduces tank temperature during idle periods.
- Alphanumeric display communicates in English and Spanish. Display capable of showing English or metric measurements.
- Compatible with BUNNlink®.

ICB-DV FEATURES



- Brews 5.1 to 11.9 gallons (19.3 to 45 litres) of perfect coffee per hour.
- Large 3-gallon (11.36 litre) tank provides back-to-back brewing capacity at 208-240V applications.
- Dual voltage adaptable. Can operate at 120V/15amp or 208-240V/20amp.
- Includes overlay kits for customization of brewer interface.

ICB-TWIN FEATURES

- Brews up to 18.9 gallons (71.5 litres) of perfect coffee per hour.
- Large 5.6 gallon (21.2 litre) tank provides back-to-back brewing capacity

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

 International electrical configurations

| Infusion Coffee Brewers | | | | | | | | | | |
|-------------------------|------------|---|------------------------|--------------|------------|------|-------|----------------------------|---------------|--|
| Model | Product # | Size | | Funnel Type | Electrical | | | Brewing Capacity | Cord Attached | Agencies |
| | | Dimension | Weight | | Volts | Amps | Watts | | | |
| ICB-DV | 36600.0000 | 26.01"H x 10.19" W x 22.42" D (66.1cm H x 25.9cm W x 57cm D) | 47.5 lbs. (21.5 kg) | Smart Funnel | 120 | 14 | 1700 | 5.1 gal. (19.3 L) | Yes |   |
| | | | | | 120/208 | 13.8 | 2900 | 8.9 gal. (33.7 L) | | |
| | | | | | 120/240 | 16.8 | 4050 | 11.9 gal. (45 L) | | |
| ICB Twin | 37600.0000 | 26.2"H x 20.0"W x 22.4"D (66.5cm H x 50.8cm W x 56.9cm D) | 77 lbs. (34.9 kg) | | 120/240 | 25 | 6000 | 18.9 gal/hr (71.5 L/hr) | | |
| | 37600.0002 | | | | 120/208 | 28 | | | | |

Infusion Coffee Brewers Tall



ICB-DV Tall
(TF Server sold separately)



ICB-Twin Tall
(TF Server sold separately)

COMMON FEATURES

- Designed to brew into 1 gallon and 1.5 gallon (3.8 and 5.7 litre) ThermoFresh® servers with base for easy transport of coffee to other locations.
- Easy Pulse interface allows automatic programming of pulse routine.
- BrewWISE® intelligence with pre-infusion and pulse brew for maximum flavor extraction. DBC grinder communicates with brewer through Smart Funnel®.
- Energy-saver mode reduces tank temperature during idle periods.
- Digital display in English/Spanish for easier programming and control. Advertising messages and machine status also displayed. Display capable of showing English or Metric measurements.
- Compatible with BUNNlink™.

ICB-DV TALL FEATURES



- Brews 5.1 to 11.9 gallons (19.3 to 45 litres) of perfect coffee per hour.
- Large 3-gallon (11.36 litre) tank provides back-to-back brewing capacity at 208-240V applications.
- Dual voltage adaptable. Can operate at 120V/15amp or 208-240V/20amp.
- Includes overlay kits for customization of brewer interface.

ICB-TWIN TALL FEATURES

- Brews up to 18.9 gallons (71.5 litres) of perfect coffee per hour.
- Large 5.6 gallon (21.2 litre) tank provides back-to-back brewing capacity

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

Infusion Coffee Brewers Tall

| Model | Product # | Size | | Funnel Type | Electrical | | | Brewing Capacity | Cord Attached | Agencies |
|---------------|------------|--|------------------------|--------------|------------|------|----------------------------|----------------------|---------------|--|
| | | Dimension | Weight | | Volts | Amps | Watts | | | |
| ICB-DV Tall | 36600.0005 | 34.4"H x 10.1"W x 19.9"D (87.4cm H x 25.7cm W x 50.5cm D) | 51 lbs. (23.1 kg) | Smart Funnel | 120 | 14 | 1700 | 5.1 gal. (19.3 L) | Yes |   |
| | | | | | 120/208 | 13.8 | 2900 | 8.9 gal. (33.7 L) | | |
| | | | | | 120/240 | 16.8 | 4050 | 11.9 gal. (45 L) | | |
| ICB Twin Tall | 37600.0005 | 34.4"H x 22.6"W x 20.1"D (87.4cm H x 57.4cm W x 51.1cm D) | 85.5 lbs. (38.8 kg) | | 25 | 6000 | 18.9 gal/hr (71.5 L/hr) | | | |

AXIOM[®] Airpot Brewers

Medium volume brewing solution featuring simple operation, precise extraction control and a variety of portable servers



AXIOM Twin APS
(airpots sold separately)



AXIOM-DV-APS
(airpot sold separately)

COMMON FEATURES

- BrewWIZARD[®] technology simplifies brewer programming with a LCD display. Set brew level, cold brew lock-out and tank temperature from the front of the machine.
- Brews directly into 1.9 to 3 liter airpots.
- Convenient airpots keep coffee hot and for hours.
- Ensures coffee brew quality with cold brew lock out capability.
- Electronic diagnostics and built in tank drain for ease of service.
- Coffee extraction controlled with programmable pre-infusion, pulse brew and digital temperature control.
- Hot water faucet.
- SplashGard[®] funnel deflects hot liquids away from the hand.
- Energy-saver mode reduces tank temperature during idle periods.


AXIOM-DV-APS FEATURES



- Easily convertible by flipping a switch to:
 - 120 volt, 12.5 amp
 - 120/208 volt, 13 amp
 - 120/240 volt, 15 amp
- Brews 4.2 to 7.5 gallons (15.7 to 28.4 litres) of perfect coffee per hour.

AXIOM-TWIN-APS FEATURES

- Brews 15 gallons (56.8 litres) of perfect coffee per hour.
- Twin brew head system.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

 International electrical configurations
(Single airpot brewer models only)

| AXIOM Coffee Brewers | | | | | | | | | | |
|----------------------|------------|--|----------------------|----------------|------------|------|-------|--------------------------|---------------|--|
| Model | Product # | Size | | Funnel Type | Electrical | | | Brewing Capacity | Cord Attached | Agencies |
| | | Dimension | Weight | | Volts | Amps | Watts | | | |
| AXIOM-DV-APS | 38700.0010 | 23.6"H x 9"W x 18.5"D (59.9cm H x 22.9cm W x 47cm D) | 36 lbs. (16.3 kg) | Plastic Funnel | 120 | 12.5 | 1500 | 4.2 gal. (15.9 L) | Yes |   |
| | | | | | 120/208 | 13 | 2680 | 7.5 gal. (28.4 L) | | |
| | | | | | 120/240 | 15 | 3550 | 7.5 gal. (28.4 L) | | |
| AXIOM Twin APS | 38700.0013 | 23.5"H x 16"W x 17.7"D (59.7cm H x 40.6cm W x 44.9cm D) | 64 lbs. (29 kg) | Stainless | 120/240 | 26 | 6100 | 15 gal/hr (56.8 L/hr) | | |

SmartWAVE® Airpot Brewers

Low profile brewer featuring SmartWAVE technology, simple operation, and flexible server options



WAVE 15-S-APS (Silver)
(thermal carafe sold separately)



WAVE 15-APS
(airpot sold separately)



legs extended to accommodate 2.5L push-button airpot

Airpot/Carafe/Pitcher Usage Table

| Brewer Position | BUNN Part # | Description | Brewer Height | Approx. Adjustment |
|-------------------------------|-------------|-----------------------------|---------------|--------------------|
| Utilizing thermal carafe tray | 36029.0001 | 1.9L deluxe thermal carafe | 16.9" | N/A |
| Utilizing thermal carafe tray | 40163.0000 | 1.9L economy thermal carafe | 16.9" | N/A |
| LP feature (Lowest) | 39430.0000 | 1.9L thermal pitcher | 16.9" | N/A |
| LP feature (Lowest) | 32125.0000 | 2.5L lever-action airpot | 16.9" | N/A |
| Extend legs | 32130.0000 | 3.0L lever-action airpot | 17.5" | .6" |
| Extend legs | 28696.0002 | 2.2L push-button airpot | 18" | 1" |
| Extend legs | 13041.0001 | 2.5L push-button airpot | 18.5" | 1.5" |
| Extend legs | 23300.0010 | 2.5L Thermal Server | 18.5" | 1.5" |

COMMON FEATURES

- Brews 3.9 gallons (14.8 litres) of perfect coffee per hour.
- Brew into 1.9L thermal carafe brewer utilizing the slide-out booster tray.
- Adjustable legs to accommodate up to 3.0L lever action and 2.5L push button BUNN airpots (refer to usage table).
- SmartWAVE® technology increases turbulence in the brew funnel.
- Convenient airpots keep coffee hot and fresh for hours and are easily transported to remote serving areas.
- Ensures coffee brew quality with cold brew lock out capability.
- Hot water faucet.
- SplashGard® funnel deflects hot liquids away from the hand.
- Energy-saver mode reduces tank temperature during idle periods.

STANDARD VERSION

- Four-digit LED read-out for simple programming.
- Utilize the same LED read-out for brewer status (Ready, Heating, Brewing).
- 13 pulse brew routine selections adjust strength profile in conjunction with the BrewMETER®.
- Large funnel to accommodate a wide range of coffees and a 17-hole sprayhead to maximise turbulence and wetting.

SILVER VERSION

- Analog switches accompanied by red/green LED for programming.
- Red/green LED provide brewer status (ready, heating, brewing).
- Choice of three pulse brew routines to adjust your flavor profile.

SmartWAVE Low Profile Airpot Brewers

| Model | Product # | Size | | Funnel Type | Electrical | | | Brewing Capacity | Cord Attached | Agencies |
|-------------------------|------------|---|----------------------|---------------|------------|------|----------------------|----------------------|---------------|----------|
| | | Dimension | Weight | | Volts | Amps | Watts | | | |
| WAVE 15-APS | 39900.0005 | 16.9"H x 8.7"W x 17.1"D (43cm H x 22.2cm W x 43.5cm D) | 24.2 lbs. (11 kg) | Black Plastic | 120 | 11.3 | 1350 | 3.9 gal. (14.8 L) | Yes | |
| WAVE 15-APS (Specialty) | 39900.0012 | | | Gourmet | | | | | | |
| WAVE 15-S-APS | 39900.0006 | | | Black Plastic | | | | | | |
| WAVE-APS | 39900.0008 | | | 120/240 | 9.4 | 2250 | 6.4 gal. (24.2 L) | No | | |
| WAVE-S-APS | 39900.0009 | | | | | | | | | |

Airpot Brewers



CWTF APS-DV (airpot sold separately) **CWTF APS** (airpot sold separately)


CWTF Twin APS (airpots sold separately)

PRODUCT FEATURES

- Brews directly into 1.9 to 3 litre airpots.
- Hot water faucet with pourover feature.
- Digital timer enables users to make brew cycle adjustments from the front panel.
- Use BUNN paper filters - Product No. 20115.0000. Gourmet funnel requires BUNN paper filter 20100.0000.

CWTF-DV FEATURES

- Voltage converts easily by flipping a switch.
- Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.*

 International electrical configurations (Single airpot brewer models only)

| CWTF and Twin Airpot Brewers | | | | | | | | | | |
|------------------------------|---------------------|--|----------------------|-----------------------------------|-------------|------|-------|-------------------------|---------------|------------------|
| Model | Product # | Size | | Funnel Type | Electrical | | | Brewing Capacity | Cord Attached | Agencies |
| | | Dimension | Weight | | Volts | Amps | Watts | | | |
| CWTF APS-DV | 23001.0058 | 23.6"H x 9"W x 18.5"D (59.9cm H x 22.9cm W x 47cm D) | 36 lbs. (16.3 kg) | Black Plastic | 120 | 11.4 | 1370 | 3.9 gal/hr 14.6 L/hr | No | |
| | | | | | 120/208 | | 2340 | 6.7 gal/hr 25.3 L/hr | | |
| | | | | | 120/240 | 13.1 | 3100 | 7.5 gal/hr 28.4 L/hr | | |
| | 23001.0059 | | 37 lbs. (16.7 kg) | Black Plastic and Stainless Steel | 120 | 11.4 | 1370 | 3.9 gal/hr 14.6 L/hr | | |
| | | | | | 120/208 | | 2340 | 6.7 gal/hr 25.3 L/hr | | |
| | | | | | 120/240 | 13.1 | 3100 | 7.5 gal/hr 28.4 L/hr | | |
| CW15-APS (no faucet) | 23001.0000 Pourover | 23.6"H x 9"W x 18.5"D (59.9cm H x 22.9cm W x 47cm D) | 28 lbs. (12.7 kg) | Black Plastic | 120 | 11.4 | 1370 | 3.8 gal/hr 14.4 L/hr | Yes | UL LISTED NSF |
| | 23001.0062 Pourover | | 29 lbs. (13.2 kg) | Black Plastic | | | | | | |
| | 23001.0003 | | 38 lbs. (17.3 kg) | Stainless Steel | | | | | | |
| CWTF15-APS | 23001.0017 | 23.6"H x 9"W x 18.5"D (59.9cm H x 22.9cm W x 47cm D) | 33 lbs. (15.0 kg) | Black Plastic | 120 | 11.4 | 1370 | 3.8 gal/hr 14.4 L/hr | Yes | UL LISTED NSF |
| | 23001.0006 | | 37 lbs. (16.8 kg) | Gourmet Funnel | | | | | | |
| | 23001.0051 | | 32 lbs. (14.6 kg) | Black Plastic | | | | | | |
| CWTF20-APS | 23001.0007 | 23.6"H x 9"W x 18.5"D (59.9cm H x 22.9cm W x 47cm D) | 33 lbs. (15.0 kg) | Black Plastic | 120 | 15 | 1850 | 5.1 gal/hr 19.3 L/hr | No | UL LISTED NSF |
| CWTF35-APS | 23001.0008 | | 37 lbs. (16.8 kg) | Gourmet Funnel | | | | | | |
| | 23001.0052 | | 37 lbs. (16.8 kg) | Stainless Steel | | | | | | |
| CWTF35-APS, SF | 23001.0023 | 23.5"H x 16"W x 19.7"D (59.7cm H x 40.6cm W x 50.0cm D) | 60 lbs. (27.3 kg) | Gourmet Funnel | 120/208-240 | 15 | 3550 | 7.5 gal/hr 28.4 L/hr | No | UL LISTED NSF |
| CWTF Twin APS | 23400.0041 | | | Stainless Steel | 120/240 | | | | | |
| | 23400.0046 | Gourmet Funnel | | | | | | | | |

Thermal Carafe Coffee Brewers



CWTF15-TC
(thermal carafe
sold separately)



AXIOM-DV-TC
(thermal carafe
sold separately)



CWTF Twin-TC
(thermal carafe
sold separately)

AXIOM-DV-TC FEATURES

- Easily convertible by flipping a switch to:
 - 120 volt, 12.5 amp
 - 120/208 volt, 13 amp
 - 120/240 volt, 15 amp
- Brews 4.2 to 7.5 gallons (15.7 to 28.4 litres) of perfect coffee per hour.
- BrewWIZARD® technology simplifies brewer programming with a LCD display. Set brew level, pulse brew, cold brew lock-out and tank temperature from the front of the machine.

CWTF-TC FEATURES

- Accepts thermal carafe up to 8.5" tall (21.6cm) (sold separately).
- Use in quick-turn environment where high quality coffee is continuously refreshed.
- SplashGard® funnel deflects hot liquids away from the hand.



International electrical configurations

CWTF TWIN-TC BREWER FEATURES

- Accepts thermal carafe up to 8.5" (21.6 cm) tall (sold separately).
- Use in quick-turn environment where high quality coffee is continuously refreshed.
- All stainless steel construction.
- SplashGard® funnel deflects hot liquids away from the hand.
- Pourover feature.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

Thermal Carafe Coffee Brewers

| Model | Product # | Size | | Electrical | | | Brewing Capacity | Funnel Type | Cord Attached | Agencies | | |
|------------------------|------------------------|--|---|----------------------|------|-------|---------------------------|---------------|---------------------------|----------|---------------------------|---------------------------|
| | | Dimension | Weight | Volts | Amps | Watts | | | | | | |
| AXIOM-DV-TC | 38700.0011 | 17.9" H x 9" W x 18.5" D (45.5cm H x 22.9cm W x 55.4cm D) | 30 lbs. (13.6 kg) | 120 | 12.5 | 1500 | 4.2 gal/hr (15.9 L/hr) | Black Plastic | Yes | | | |
| | | | | 120/208 | 13 | 2680 | 7.5 gal/hr (28.4 L/hr) | | | | | |
| | | | | 120/240 | 15 | 3550 | 7.5 gal/hr (28.4 L/hr) | | | | | |
| CW15-TC (no faucet) | 23001.0040 Pourover | 17.9" H x 9" W x 18.5" D (45.5cm H x 22.9cm W x 55.4cm D) | 28 lbs. (12.7 kg) | 120 | 11.4 | 1370 | 3.9 gal/hr (14.6 L/hr) | No | | | | |
| CWTF15-TC | 12950.0360 | | 32 lbs. (14.5 kg) | | | | 120 | | 15.4 | | 1850 | 5.3 gal/hr (19.9 L/hr) |
| CWTF20-TC | 12950.0380 | | 31 lbs. (14.1 kg) | 120/208-240 | 15 | 3550 | | | | | | 7.5 gal/hr (28.4 L/hr) |
| CWTF35-TC | 12950.0379 | | 32 lbs. (14.5 kg) | | | | | | | | | 120/240 |
| CWTF Twin-TC | 23400.0047 | | 17.2" H x 16" W x 22.5" D (43.7cm H x 41cm W x 57.2cm D) | 64 lbs. (29.3 kg) | 120 | 11.4 | 2340 | | 3.9 gal/hr (14.6 L/hr) | | | |
| CWTF-TC DV | 23001.0069 | 17.9" H x 9" W x 18.5" D (45.5cm H x 22.9cm W x 55.4cm D) | 29 lbs. (13.2 kg) | 120/208 | | | | 13.1 | 3100 | | 6.7 gal/hr (25.3 L/hr) | |
| | | | | | | | | | | | 7.5 gal/hr (28.4 L/hr) | |

Airpots and Thermal Carafes



Push-Button Airpot



Lever-Action Airpot



Thermal Carafe



Economy Thermal Carafe



Vacuum Pitcher

PUSH-BUTTON AIRPOT FEATURES

- Brew-through pump assembly
- Just close the lid after brewing – dispenses up to 4 ounces (.12 litres) at the first pump.
- Glass insulation keeps beverage hot.

LEVER-ACTION AIRPOT FEATURES

- Stainless steel lining keeps coffee hot.
- Brew-through lid with lever-action for easy use.

THERMAL CARAFE FEATURES

- Holds 1.9 litres or 64 ounces (12 cups) of coffee or other hot beverage.
- Unbreakable stainless steel interior and exterior.
- Superior vacuum insulation keeps beverages hot for hours.
- Brew-through lid allows direct brewing.
- Fits on BUNN Thermal Carafe and Twin Thermal Carafe brewers.

See page 64 for universal airpot racks and coffee-isers.

| Airpots & Thermal Carafes | | | | | | | |
|---|------------|---|--------------------|-----------------|----------------|-------------------------|----------|
| Model | Product # | Size | | Liner | Quantity | Capacity | Agencies |
| | | Dimension | Weight | | | | |
| 2.2 litre Push-Button Airpot | 28696.0002 | 16.4" H x 6.1" W x 7.9" D (42cm H x 16cm W x 20cm D) | 4.5 lbs. (2.04 kg) | Glass | single unit | 2.2 litres (74 oz) | ETL |
| | 28696.0000 | | 24 lbs. (10.9 kg) | | 6 units/ case | | |
| 2.5 litre Push-Button Airpot | 13041.0001 | 14.6" H x 6.3" W x 9" D (37cm H x 16cm W x 23cm D) | 5 lbs. (2.3 kg) | Glass | single unit | 2.5 litres (84 oz.) | NSF |
| | 13041.0101 | | 25 lbs. (11.3 kg) | | 6 units/ case | | |
| 2.5 litre Lever-Action Airpot | 32125.0000 | 14.6" H x 6.3" W x 9" D (37cm H x 16cm W x 23cm D) | 5.3 lbs. (2.4 kg) | Glass | single unit | 2.5 litres (84 oz.) | NSF |
| | 32125.0100 | | 32 lbs. (14.6 kg) | | 6 units/ case | | |
| 3.0 litre Lever-Action Airpot | 32130.0000 | 15.5" H x 6.3" W x 9" D (39.4cm H x 16cm W x 23cm D) | 5.8 lbs. (2.6 kg) | Glass | single unit | 3.0 litres (102 oz.) | NSF |
| | 32130.0100 | | 35 lbs. (15.9 kg) | | 6 units/ case | | |
| 3.8 litre Lever-Action Airpot | 36725.0000 | (17.6" H x 6.3" W x 9" D) (44.7cm H x 16cm W x 23cm D) | 7 lbs. (3.2 kg) | Glass | single unit | 3.8 litres (128 oz) | NSF |
| | 36725.0100 | | 41 lbs. (18.6 kg) | | 6 units/ case | | |
| 1.9 litre Thermal Carafe (Black Lid) | 36029.0001 | 8" H x 6.4" W x 8.2" D (20.3cm H x 16.3cm W x 21cm D) | 3.0 lbs. (1.36 kg) | Stainless Steel | single unit | 1.9 litres (64 oz.) | NSF |
| | 36029.0000 | | 34 lbs. (15.4 kg) | | 12 units/ case | | |
| 1.9 litre Thermal Carafe (Orange Lid) | 36252.0001 | 8" H x 6.4" W x 8.2" D (20.3cm H x 16.3cm W x 21cm D) | 3.0 lbs. (1.36 kg) | Stainless Steel | single unit | 1.9 litres (64 oz.) | NSF |
| | 36252.0000 | | 34 lbs. (15.4 kg) | | 12 units/ case | | |
| 1.9 litre Economy Thermal Carafe (Black Lid) | 40163.0000 | 7.1" H x 6.6" W x 8.64" D (18cm H x 16.8cm W x 21.9cm D) | 2.5 lbs. (1.1 kg) | Stainless Steel | single unit | 1.9 litres (64 oz.) | NSF |
| | 40163.0100 | | 30 lbs. (13.6 kg) | | 12 units/ case | | |
| 1.9 litre Economy Thermal Carafe (Orange Lid) | 40163.0001 | 7.1" H x 6.6" W x 8.64" D (18cm H x 16.8cm W x 21.9cm D) | 2.5 lbs. (1.1 kg) | Stainless Steel | single unit | 1.9 litres (64 oz.) | NSF |
| | 40163.0101 | | 30 lbs. (13.6 kg) | | 12 units/ case | | |
| 1.9 litre Vacuum Pitcher (Black Lid) | 39430.0000 | 11.3" H x 6.5" W x 5.5" D (28.7cm H x 16.5cm W x 14cm D) | 3.0 lbs. (1.36 kg) | Stainless Steel | single unit | 1.9 litres (64 oz.) | NSF |
| | 39430.0100 | | 17 lbs. (7.71 kg) | | 6 units/ case | | |

Thermal Coffee Brewers, Servers and Stands



CWTF-TS
(Server sold separately)



TSR-1 and TSR-2
(shown with
TS servers no base)



TS Booster



TSR
(Raised)

PRODUCT FEATURES

- Pourover feature included on automatic brewer models.
- Internal stainless steel components.
- Hot water faucet available.
- SplashGard® funnel deflects hot liquids away from the hand.
- Holds up to 4" (10.16 cm) tall cup.
- Use BUNN paper filters – Product No. 20115.0000.

THERMAL SERVER FEATURES



- Convenient for keeping coffee hot and for hours.
- Easily transported to remote locations.
- Depending on base, server can hold up to 6½" (16.51 cm) cup.

THERMAL SERVER RACK FEATURES


- Holds one or two 2.5 litre thermal servers without base.
- Made of durable, easy-to-clean plastic with drip trays to catch spills and keep serving areas clean.

 International electrical configurations

Thermal Server Coffee Brewers

| Model | Product # | Size | | Electrical | | | Brewing Capacity | Cord Attached | Agencies |
|--------------------------------|------------|--|-------------------|------------|------|-------|----------------------------|---------------|--|
| | | Dimension | Weight | Volts | Amps | Watts | | | |
| CW15-TS (Pourover) | 23000.0000 | 27.6" H x 9" W x 18.5" D (70.1cm H x 22.9cm W x 47cm D) | 27 lbs. (12.3 kg) | 120 | 11.4 | 1370 | 3.9 gal/hr. (14.6 L/hr) | Yes |   |
| CWTF15-TS (Automatic w/faucet) | 23000.0006 | | 32 lbs. (14.6 kg) | | | | | | |

Thermal Servers and Stands

| Model | Product # | Size | | Capacity | Quantity | Agencies |
|------------------------------|------------|---|-------------------|-------------------------------|-------------|---|
| | | Dimension | Weight | | | |
| TS | 23300.0007 | 19.6" H x 7.9" W x 8.7" D (49.8cm H x 20.1cm W x 22.1cm D) | 6 lbs. (2.7 kg) | 2.5 litres (84 oz.) | single unit |  |
| | 23300.0005 | | 33 lbs. (15 kg) | | 6/case | |
| TSR (Raised) | 23300.0009 | 21.8" H x 7.9" W x 8.9" D (55.4cm H x 20cm W x 22.6cm D) | 6 lbs. (2.7 kg) | | single unit | |
| TS (no base) | 23300.0010 | 14.4" H x 7" W x 8.1" D (36.6cm H x 17.8cm W x 20.6cm D) | 4 lbs. (1.8 kg) | | 6/case | |
| | 23300.0006 | | 25 lbs. (11.3 kg) | | | |
| BUNN Safety-Fresh® Lid (Kit) | 22964.0000 | n/a | 1 lb. (.5kg) | | single unit | |
| TSR-1 | 18008.6001 | 25" H x 7.5" W x 8.5" D (63.5cm H x 19.1cm W x 21.6cm D) | 4.5 lbs. (2.1 kg) | 1 Thermal Server w/out Base | n/a | |
| TSR-2 | 18008.6002 | 28.5" H x 7.5" W x 17" D (72.4cm H x 19.1cm W x 43.2cm D) | 8 lbs. (3.6 kg) | 2 Thermal Servers w/out Bases | | |
| TS Booster | 18010.6000 | 6" H x 9.25" W x 8.25" D (15.2cm H x 23.5cm W x 21cm D) | 2 lbs. (.9 kg) | 1 Thermal Server w/out Base | | No Lis ing |