

AXIOM® Coffee Brewers

Medium volume brewing solution featuring simple operation, precise extraction control and a variety of portable servers

Automatic
Decanter Coffee Brewers and Urns



AXIOM-DV-3
(2 upper warmers,
1 lower warmer - 2U, 1L)
(Decanters sold separately)



PRODUCT FEATURES

- Large 200 oz. (5.9 litres) tank provides back-to-back brewing capacity.
- Dual voltage available on some models. Can operate at 120V/15 amp or 120/208-240V/20 amp.
- Adjusts automatically to varying water pressure.
- BrewLOGIC® technology calculates flow rate and adjusts brew time to maintain consistent pot levels even in high lime areas.
- BrewWIZARD® technology simplifies brewer programming with a LCD display. Set brew level, cold brew lock-out and tank temperature from the front panel.
- Digital temperature control and accuracy.
- Ensures coffee brew quality with cold brew lock out capability.
- Electronic diagnostics and built in tank drain make service easier.
- SplashGard® funnel deflects hot liquids away from the hand.
- Coffee extraction controlled with programmable pre-infusion, pulse brew and digital temperature control.
- Automatic warmer shut-off.
- Energy-saver mode reduces tank temperature during idle periods.
- Use BUNN paper filters – Product No. 20115.0000.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

 International electrical configurations

AXIOM Coffee Brewers with Upper/Lower Warmers

Model	Product #	Size		Electrical			Brewing Capacity	Funnel Type	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts				
AXIOM-15-3	38700.0000	18.9"H x 8.5"W x 17.7"D (49cm H x 21.6cm W x 44.9cm D)	30 lbs. (13.6 kg)	120	15	1800	4.2 gal/hr 15.9 L/hr	Plastic	Yes	 
AXIOM-35-3	38700.0001			120/240	17.5	3850	7.5 gal/hr 28.4 L/hr		No	
AXIOM-DV-3	38700.0008			120	15	1800	4.2 gal/hr 15.9 L/hr		Yes	
				120/208	15.5	2980	7.5 gal/hr 28.4 L/hr			
				120/240	17.5	3850				

AXIOM[®] Coffee Brewers

Medium volume brewing solution featuring simple operation, precise extraction control and a variety of portable servers





AXIOM-15-3
(3 lower warmer - 3L)
(Decanters sold separately)

PRODUCT FEATURES

- Large 200 oz. (5.9 litres) tank provides back-to-back brewing capacity.
- Adjusts automatically to varying water pressure.
- For high lime areas, BrewLOGIC[®] technology calculates flow rate and adjusts brew time to maintain consistent pot levels.
- BrewWIZARD[®] technology simplifies brewer programming with a LCD display. Set brew level, cold brew lock-out and tank temperature from the front panel.
- Electronic diagnostics and built in tank drain make service easier.
- Ensures coffee brew quality with cold brew lock out capability.
- SplashGard[®] funnel deflects hot liquids away from the hand.
- Coffee extraction controlled with pre-infusion, pulse brew and digital temperature control.
- Automatic warmer shut-off.
- Energy-saver mode reduces tank temperature during idle periods.
- Hot water faucet.
- Dual voltage available. Can operate at 120V/15 amp or 120/208-240V/20 amp.
- Use BUNN paper filters – Product No. 20115.0000.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

AXIOM Coffee Brewers with Lower Warmers

Model	Product #	Size		Electrical			Brewing Capacity	Funnel Type	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts				
AXIOM-15-3	38700.0002	16.8"H x 16.5"W x 17.7"D (42.7cm H x 41.9cm W x 45cm D)	31 lbs. (14.1 kg)	120	15	1800	4.2 gal/hr 15.9 L/hr	Plastic	Yes	 
AXIOM-35-3	38700.0003			120/240	17.5	3850	7.5 gal/hr 28.4 L/hr		No	
AXIOM-DV-3	38700.0009	18.9"H x 8.5"W x 17.7"D (48cm H x 21.6cm W x 44.9cm D)	32 lbs. (14.5 kg)	120	15	1800	4.2 gal/hr 15.9 L/hr		Yes	
				120/208	15.5	2980	7.5 gal/hr 28.4 L/hr			
				120/240	17.5	3850				

Decanter Coffee Brewers



CWTF
(2 upper warmers,
1 lower warmer - 2U, 1L)
(Decanters sold separately)




CWTF
(1 upper warmer,
1 lower warmer - 1U, 1L)
(Decanters sold separately)



PRODUCT FEATURES

- All stainless steel construction.
- CWTF models feature hot water faucet and pourover backup on all models.
- SplashGard® funnel deflects hot liquids away from the hand.
- Use BUNN paper filters – Product No. 20115.0000.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

 International electrical configurations (CWTF only)

12 Cup Coffee Brewers with Upper/Lower Warmers

Model	Product #	Size		Electrical			Brewing Capacity	Funnel Type	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts				
CWTF15	12950.0211 (1U, 1L)	18.9"H x 8.5"W x 17.8"D (48cm H x 21.6cm W x 45.2cm D)	32.5 lbs. (14.5 kg)	120	13	1570	3.9 gal/hr 14.6 L/hr	Plas ic	Yes	 
CWT15 (no faucet)	12950.0356 (2U, 1L)		30 lbs. (13.6 kg)		13.9	1670				
CWT20 (no faucet)	12950.0291 (2U, 1L)				17.9	2150	5.3 gal/hr 19.9 L/hr	Stainless	No	
CWT35 (no faucet)	12950.0292 (2U, 1L)			120/208- 240	17.1	3850	7.5 gal/hr 28.4 L/hr			
CWTF15-3	12950.0213 (2U, 1L)		33 lbs. (14.97 kg)	120	13.9	1670	3.9 gal/hr 14.6 L/hr	Plas ic	Yes	
	12950.0217 (2U, 1L)		34 lbs. (15.4 kg)							
CWTF20-3	12950.0283 (2U, 1L)		31 lbs. (14.1 kg)	120/240	17.1	3850	5.3 gal/hr 19.9 L/hr	Stainless	No	
CWTF35-3	12950.0253 (2U, 1L)		30 lbs. (13.6 kg)							
	12950.0261 (2U, 1L)		32 lbs. (14.5 kg)							
CWTF-DV	12950.0410 (2U, 1L)		35 lbs. (15.9 kg)	120	13.9	1670	3.9 gal/hr 14.6 L/hr	Stainless	No	
		120/208		13.9	2640	6.7 gal/hr 25.3 L/hr				
		120/240		15.6	3400	7.5 gal/hr 28.4 L/hr				

Decanter Coffee Brewers



CWTF
(3 lower warmers - 3L)
(Decanters sold separately)




A10
(Includes decanter)

PRODUCT FEATURES

- All stainless steel construction.
- CWTF models feature pourover backup on all models.
- SplashGard® funnel deflects hot liquids away from the hand.
- Use BUNN paper filters – Product No. 20115.0000.
- Low profile for under cabinet placement.



Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

 International electrical configurations (CWTF only)

A10 MODEL FEATURES

- Uses 50 oz. decanter.
- Use BUNN paper filters - Product No. 20106.0000.

12 Cup Coffee Brewers with Lower Warmers

Model	Product #	Size		Electrical			Brewing Capacity	Funnel Type	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts				
CWTF15	12950.0293 (1L)	16.8"H x 8.5"W x 17.8"D (42.7cm H x 21.6cm W x 45.2cm D)	27 lbs. (12.2 kg)	120	12.3	1470	3.9 gal/hr 14.6 L/hr	Plastic	Yes	 
CWTF15 (left warmers)	12950.0298 (3L)		35 lbs. (15.9 kg)		13.9	1670				
CWTF35	12950.0381 (3L)	39 lbs. (17.7 kg)	120/208-240	17.1	3850	7.5 gal/hr 28.4 L/hr	Stainless	No		
CWT15-3 (no faucet)	12950.0112 (3L)	32 lbs. (14.5 kg)	120	13.9	1670	3.9 gal/hr 14.6 L/hr	Plastic	Yes		
CWTF15-3	12950.0212 (3L)	35 lbs. (15.9 kg)								
	12950.0216 (3L)	36 lbs. (16.4 kg)								
CWTF20-3	12950.0232 (3L)	17"H x 16.5"W x 17.7"D (43.3cm H x 41.9cm W x 45.2cm D)	35 lbs. (15.9 kg)	120/240	16	3850	5.3 gal/hr 19.9 L/hr	Plastic	No	
CWTF35-3	12950.0252 (3L)									
CWTF-DV	12950.0409 (3L)	14.7" H x 6.7" W x 12.9" D (37.3cm H x 17.0cm W x 32.8cm D)	39 lbs. (17.7 kg)	120	15	1800	3.9 gal/hr 14.6 L/hr	Stainless	No	
				120/208	15.5	2980	6.7 gal/hr 25.3 L/hr			
				120/240	17.5	3850	7.5 gal/hr 28.4 L/hr			
A10A (pourover)	21250.0004	16 lbs. (7.3 kg)	120	9.5	1140	2.9 gal/hr 11 L/hr	Black	Yes		

Decanter and AXIOM® Coffee Brewers

Medium volume brewing solution featuring simple operation, precise extraction control and a variety of portable servers



CWTF Twin
(0/6 Twin)
(Decanters sold separately)



CWTF Twin
(2/2 Twin)
(Decanters sold separately)



AXIOM Twin
(0/6 Twin)
(Decanters sold separately)



AXIOM Twin
(4/2 Twin)
(Decanters sold separately)


CWTF FEATURES

- Medium volume, twin brew head systems.
- Four or six individually controlled warming stations.
- All stainless steel construction.
- Pourover feature on both sides.
- SplashGard® funnel deflects hot liquids away from the hand.
- Use BUNN paper filters - Product No. 20115.0000.



AXIOM FEATURES

- Twin brew head systems.
- Brews 15 gallons (56.8 litres) of perfect coffee per hour.
- Six individually controlled warmers.
- For high lime areas, BrewLOGIC® technology calculates flow rate and adjusts brew time to maintain consistent pot levels.
- BrewWIZARD® technology simplifies brewer programming with a LCD display. Set brew level, cold brew lock-out and tank temperature from the front panel.
- Ensures coffee brew quality with cold brew lock out capability.
- SplashGard® funnel deflects hot liquids away from the hand.
- Electronic diagnostics and built-in tank drain make service easier.
- Coffee extraction controlled with programmable pre-infusion and pulse brew features.
- Use BUNN paper filters – Product No. 20115.0000.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

 International electrical configurations (CWTF only)

12 Cup Coffee Brewers with 4 or 6 Warmers

Model	Product #	Size		Electrical			Legs	Brewing Capacity	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts				
CWTF 2/2 Twin	23400.0001	19.3"H x 16.5"W x 19.8"D (49cm H x 41.9cm W x 50.3cm D)	56 lbs. (25.4 kg)	120/240	27.7	6650	n/a	15 gal/hr 56.8 L/hr	No	 
CWTF 4/2 Twin	23400.0011				28.5	6850				
CWTF 0/6 Twin	23400.0020	20.54" H x 30.75" W x 20.64" D (52.17cm H x 78.11cm W x 50.43cm D)	74 lbs. (33.6 kg)		28.5	6850	4" satin nickel legs			
AXIOM 4/2 Twin	38700.0014	19.1"H x 16.4"W x 17.7"D (48.5cm H x 41.7cm W x 44.9cm D)	61 lbs. (27.7 kg)	120/ 208-240	27.9	6700	n/a			
AXIOM 0/6 Twin	38700.0015	20.5" H x 30.3" W x 17.7" D (52.1cm H x 77cm W x 45cm D)	74 lbs. (33.6 kg)				4" black legs			

Automatic Brewers



OL
(Decanters sold separately)

OT
(Decanters sold separately)

OT/OL FEATURES

- Two separately controlled warmers.
- Designed to function well in low or uneven water pressure situation. (OL models)
- All stainless steel construction.
- OL models can also be operated as a pourover unit.
- Faucet kit available.
- SplashGard® funnel deflects hot liquids away from the hand.
- Use BUNN paper filters - Product No. 20115.0000.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.





VLPF
(Decanters sold separately)

VLPF FEATURES

- Internal stainless steel components.
- Two individually controlled warmers.
- SplashGard® deflects hot liquids away from the hand.
- Use BUNN paper filters - Product No. 20115.0000.

Automatic Brewer with 2 Warmers

Model	Product #	Size		Electrical			Brewing Capacity	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts			
OL 20	20820.0001	23.5" H x 12" W x 18.5" D (59.7cm H x 30.5cm W x 47cm D)	34 lbs. (15.5 kg)	120	17	2050	6 gal/hr 22.7 L/hr	No	 
OL 35	20820.0002			120/240	15.6	3750	7.5 gal/hr 28.4 L/hr		
OT 15	20830.0000	22.4" H x 12" W x 18.3" D (56.9cm H x 30.5cm W x 46.5cm D)	32.7 lbs. (14.8 kg)	120	13	1570	4.2 gal/hr 15.7 L/hr	Yes	
OT 20	20830.0001				17.4	2090	5.3 gal/hr 19.9 L/hr	No	
VLPF	07400.0005	17.4" H x 23.5" W x 13.1" D (44.2cm H x 59.7cm W x 33.3cm D)	26.3 lbs. (11.9 kg)	120	13.3	1600	3.9 gal/hr 14.6 L/hr	Yes	

Decanter Coffee Brewers




CRTF
(Decanters sold separately)

PRODUCT FEATURES

- Five separately controlled warmers.
- All stainless steel construction.
- Models available with faucet. Faucet kits available for existing models.
- SplashGard® funnel deflects hot liquids away from the hand.
- Designed to function well in low water pressure situations, the RL model can also be operated as a pourover unit.
- CRTF model has hot water faucet and pourover feature.
- Use BUNN paper filters - Product No. 20115.0000.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

 International electrical configurations (RL only)





RL
(Decanters sold separately)



RT
(Decanters sold separately)

12 Cup Coffee Brewer with 5 Warmers

Model	Product #	Size		Electrical			Funnel Type	Brewing Capacity	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts				
CRTF5-35	13250.0023	17.1" H x 24 5" W x 18.2" D (43.4cm H x 62.2cm W x 46.2cm D)	50.2 lbs. (22.8 kg)	120/240	16.9	4050	Plastic	7.5 gal/hr 28.4 L/hr	No	 
CRTF5-35	13250.0025		48 lbs. (21.8 kg)							
RT	20835.0000	21.2" H x 24" W x 18.5" D (53.8cm H x 61cm W x 47cm D)	42 lbs. (19.1 kg)							
RTF (w/faucet)	20835 0004	46 lbs. (20.9 kg)								
RL	20825 0000	23.5" H x 24" W x 18.5" D (59.7cm H x 61cm W x 47cm D)	44 lbs. (20.0 kg)							

Coffee Urns



SRU

3 GALLON URN FEATURES

- Automatic drip brewing of delicious coffee every time.
- Large water tank holds over 10 gallons.
- Draw off hot water during brewing cycle without affecting delivery of coffee.
- All stainless steel construction.
- Brews full or half batches.
- Top mounted components ease service.
- Use BUNN paper filters - Product No. 20109.0000.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.



International electrical configurations

TWIN 3 GALLON FEATURES

- Unique design assures extremely low evaporation loss to maintain the brew at its flavorful peak.
- Large water tank holds over 20 gallons.
- Draw off hot water during brewing cycle without affecting coffee quality.
- Half-batch option.
- Top mounted components ease service.
- All stainless steel construction.
- Use BUNN paper filters - Product No. 20109.0000.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.







International electrical configurations



U3

Coffee Urns

Model	Product #	Size		Electrical			Capacity	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts			
SRU	06325.0001	33.5" H x 14" W x 24.6" D (85.1cm H x 35.6cm W x 62.5cm D)	73 lbs. (33.1 kg)	120/208	19.4	4025	11.4 gal/hr.	No	 
	06325.0002		75 lbs. (34.0 kg)	120/240	16.8				
U3 (Single Serve)	20500.0000	32.4" H x 34.5" W x 21" D (82.3cm H x 87.6cm W x 53.3cm D)	103 lbs. (46.8 kg)	120/208	28	5825	16.3 gal/hr.	No	 
	20500.0001		120/240	6725		18.8 gal/hr.			