


Precise Temperature Water Dispensers





PRODUCT FEATURES

- Pourover model tank size: 80 oz. (2.37 litres)
- Precise temperature 72°-212°F (22.2°C-100°C) ensures consistent results. (OHW models)
- High quality, easy-to-clean stainless steel exterior and tank for a long life.
- Includes drip tray. (HW2 and OHW models)
- Includes dry-plug prevention for easy installation. (H10X models)
- Pourover model plugs into any 120 volt outlet, no plumbing needed.
- H5 models can be front or side wall mounted.
- Drip tray available for H5 models. Product No. 02497.0000



 International electrical configurations (HW2, H5 and HW10 models)

Precise Temperature Water Dispensers

Pourover & Medium Volume Machines

Model	Product #	Size		Electrical			°F Settings	Capacity	Cord Attached	Agencies
		Dimension	Weight	Volts	Amps	Watts				
OHW	02550.0003	16.9" H x 6.5" W x 10.8"D (42.9cm H x 16.8cm W x 27.4cm D)	13 lbs. (5.9 kg)	120	8.6	1040	200	80 oz. 2.37 L	Yes	 
HW2	02500.0001	24" H x 7.1" W x 14.3"D (60.96cm H x 18.03cm W x 36.3cm D)	23 lbs. (10.43 kg)		15	1800		4.2 gal/hr. 15.9 L/hr.		
HW2 Black	02500.0005									

Large Volume Machines

Model	Product #	Size		Electrical			°F Settings	cold water input 35°	hot water input 140°	Cord Attached	Agencies		
		Dimension	Weight	Volts	Amps	Watts							
H5E-18-120	12500.0020	28.5" H x 7.1" W x 17.5" D (72.4cm H x 18.03cm W x 44.5cm D)	32 lbs. (14.1 kg)	120	15.4	1850	85/115	varies with application		No	 		
	12500.0033						72						
H5E-40-240	12500.0024			240	16.9	4050	200					3.7 gal/hr. 14 L/hr.	8.1 gal/hr. 31 L/hr.
H5E-40-208	12500.0025			208	19.5								
H5E-DV PC	39100.0000			120	15.4	1850	90					3.7 gal/hr. 14 L/hr.	n/a
	39100.0001			240	16.9	4050						7.3 gal/hr. 27.6 L/hr.	14.7 gal/hr. 55.6 L/hr.
H5X-DV PC	39100.0005		240	16.9	4050	212	7.3 gal/hr. 27.6 L/hr.	14.7 gal/hr. 55.6 L/hr.					
H5X-40-240	12500.0026		208	19.5			3.7 gal/hr. 14 L/hr.	8.1 gal/hr. 31 L/hr.					
H5X-40-208	12500.0027		32 lbs. (14.1 kg)	208	19.5	8050	212	3.7 gal/hr. 14 L/hr.	8.1 gal/hr. 31 L/hr.				
H5X-18-120	12500.0028		120	15.4	1850			9.9 gal/hr. 37.5 L/hr.	18.6 gal/hr. 70.4 L/hr.				
H5X-60-208	12500.0032	33 lbs. (15.0 kg)	208	29	200	212	3.7 gal/hr. 14 L/hr.	8.1 gal/hr. 31 L/hr.					
H5M-18-120	12500.0046	120	15.4	1850			7.3 gal/hr. 27.6 L/hr.	14.7 gal/hr. 55.6 L/hr.					
H10X-80-208	26300.0001	34.4" H x 10.2" W x 24.5"D (87.4cm H x 25.9cm W x 62.2cm D)	66.7 lbs. (30.3 kg)	208	38.7	8050	212	13.2 gal/hr. 50 L/hr.	24.8 gal/hr. 93.9 L/hr.				
H10X-80-240	26300.0000			240	33.5			3.7 gal/hr. 14 L/hr.	8.1 gal/hr. 31 L/hr.				